



Embassy of the Republic of the Philippines  
Pasuguan ng Pilipinas  
Seoul

## **REQUEST FOR QUOTATION**

The Philippine Embassy in Seoul, Republic of Korea is inviting companies to submit quotations for its procurement of one (1) brand-new CCTV camera unit for the Chancery, in accordance with the "Guidelines for the Procurement of Goods and Services, Infrastructure Projects and Consulting Services to be Procured and Performed Overseas", as approved by the Government Procurement Policy Board (GPPB) in its Resolution No. 28-2017 dated 31 July 2017.

The terms of reference of the project are listed on **Annex A**. Aside from the quotation, interested companies are required to fill-out **Annex B**, which contains the checklist of technical specifications, and submit with the quotation. Incomplete submissions (*quotation without filled-out Annex B or vice versa*) shall be considered ineligible.

The last day for the submission of quotations is on 22 December 2022, at 5:00 p.m. Interested suppliers may send their duly signed quotations to **seoulpe@philembassy-seoul.com** and attention it to **Ms. Anna Gabriella E. Guinto**.

Furthermore, interested companies may set-up a schedule for an ocular inspection with Ms. Guinto to inspect the location where the new CCTV dome care units shall be installed.

For further inquiries, please contact the Philippine Embassy at telephone number (02)796-7387 ext. 312.

The Embassy of the Philippines  
Seoul, Republic of South Korea

20 December 2022

**ANNEX A**

**SUPPLY AND INSTALLATION OF ONE (1) BRAND-NEW CCTV CAMERA UNITS**

**Terms of Reference**

The Embassy of the Philippines intends to purchase and install one (1) brand-new CCTV camera units in the chancery from a reputable Company.

**I. Technical Specification**

The CCTV camera should meet the minimum specifications listed below:

<b><u>IMAGE</u></b>	
<i>Lens</i>	Motorized Varifocal 2.8~12mm, F1.4
<i>Angle of View</i>	94 °(H)~34°(H)
<i>Image Sensor Type</i> <i>Pixels</i>	½.9" Sony Exmor CMOS 1984(H)x1125(V)
<i>Min. Illumination</i>	Color: 0.1Lux@F2.1 / BW: 0Lux@F2.1 (IR LED On)
<i>Scanning Mode</i>	Progressive Scan
<i>Wide Dynamic Range</i>	Yes
<i>Day and Night Mode</i>	True D/A (Auto, Day, Night)
<i>Noise Reduction</i>	2DNR, 3DNR
<i>Digital Zoom</i>	ROI
<i>Exposure Control</i>	Auto
<i>White Balance Control</i>	Auto, Manual
<i>Back Light Compensation</i>	Yes
<i>Image Effect</i>	Flip, Mirror, Defog
<i>Flicker Free Mode</i>	50Hz, 60Hz
<i>Shutter Speed</i>	Auto (1/10,000~1sec), Manual
<i>IR Illuminator Quantity</i> <i>Angle</i> <i>Distance</i>	24 IR LEDs 90/30 °(H) 30m
<b><u>VIDEO/AUDIO</u></b>	
<i>Compression</i>	H.264(Baseline, Main, High Profile), MJPEG
<i>Bitrate Control</i>	CBR, CVBR
<i>Resolution</i>	1920x1080, 1280x1024, 1280x720/960, 1024x768, 704x480/576, 640x480, 320x240
<i>Frame Rate</i>	Max. 30/25fps (NTSC/PAL)

**ANNEX A**

<i>Streaming</i>	Triple Stream: H.264x/H.265x2, MJPEGx1
<b><u>SYSTEM</u></b>	
<i>Video Contents Analysis</i>	Tampering
<i>Motion Detection Area</i>	16 Programmable Area (Include Area 8, Exclude Area 8)
<i>Privacy Mask Zone</i>	4 Programmable Zone
<i>Smart Codec ROI</i>	8 Regions
<i>FTP Uploading</i>	MJPEG
<i>Event Notification</i>	E-mail, FTP, Notification Server, XML Notification
<i>Login Authority</i>	Administrator, Operator, Guest
<i>Event Buffering FTP</i>	Pre: 30sec, Post: 30sec
<i>Manual Trigger</i>	4 Programmable Trigger
<i>Security</i>	Multi User Authority, IP Filtering, HTTPS, SSL
<i>Network Time Sync</i>	NTP Server, Synchronized Computer, Manual
<i>Software Reset</i>	Restart, Reset, Factory Default
<i>Hardware Factory Reset</i>	Yes
<i>Auto Recovery</i>	Backup, Restore
<i>Remote Upgrade</i>	Web Browsing (IE, Chrome, Safari, Firefox), SmartManager
<b><u>NETWORK</u></b>	
<i>Protocol</i>	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, QoS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
<i>Client Software</i>	Web, SmartManager, Client S/W, Mobile S/W
<i>Max. User Connection</i>	Live: 10 users, Playback: 3 users
<i>API Support</i>	Open API, Onvif Compliance
<i>Mobile Support</i>	Android, iOS
<b><u>EXTERNAL IN/OUT</u></b>	
<i>Ethernet</i>	RJ-45(10/100Base-T)
<b><u>ETC</u></b>	
<i>Operating Humidity</i>	95% or less (Non-Condensing)
<i>Operating Temperature</i>	-20~+50°C
<i>Power Supply</i>	PoE/12VDC
<i>Power Consumption</i>	145mA(7W)@PoE / 480mA(5.8W)@12VDC
<i>Dimension</i>	81(W)x82(H)x239(D)mm
<i>Net Weight</i>	Approx. 680g
<i>Ingress Protection</i>	IP66

## **ANNEX A**

### **II. Scope of Work**

The Company shall be responsible of the following:

1. Dismantling of the old CCTV camera
2. Supplying and installing one (1) CCTV cameras

### **III. Deliverable**

The Company shall supply and install one (1) CCTV camera in the Embassy of the Philippines (80 Hoenamu-ro, Yongsan-gu, Seoul)

### **IV. Warranty**

The product shall include at least one (1) year warranty beginning from project completion date.

### **V. Terms of Payment**

Payment shall be made within fifteen (15) days upon completion of delivery and installation of one (1) CCTV camera.

**ANNEX B****CHECKLIST OF TECHNICAL SPECIFICATIONS**

1. Model of CCTV Camera: \_\_\_\_\_
2. Does the product meet the minimum specifications listed below:

<b><u>IMAGE</u></b>	
<i>Lens</i>	Motorized Varifocal 2.8~12mm, F1.4
<i>Angle of View</i>	94 °(H)~34°(H)
<i>Image Sensor Type</i> <i>Pixels</i>	½.9" Sony Exmor CMOS 1984(H)x1125(V)
<i>Min. Illumination</i>	Color: 0.1Lux@F2.1 / BW: 0Lux@F2.1 (IR LED On)
<i>Scanning Mode</i>	Progressive Scan
<i>Wide Dynamic Range</i>	Yes
<i>Day and Night Mode</i>	True D/A (Auto, Day, Night)
<i>Noise Reduction</i>	2DNR, 3DNR
<i>Digital Zoom</i>	ROI
<i>Exposure Control</i>	Auto
<i>White Balance Control</i>	Auto, Manual
<i>Back Light Compensation</i>	Yes
<i>Image Effect</i>	Flip, Mirror, Defog
<i>Flicker Free Mode</i>	50Hz, 60Hz
<i>Shutter Speed</i>	Auto (1/10,000~1sec), Manual
<i>IR Illuminator Quantity</i> <i>Angle</i> <i>Distance</i>	24 IR LEDs 90/30 °(H) 30m
<b><u>VIDEO/AUDIO</u></b>	
<i>Compression</i>	H.264(Baseline, Main, High Profile), MJPEG
<i>Bitrate Control</i>	CBR, CVBR
<i>Resolution</i>	1920x1080, 1280x1024, 1280x720/960, 1024x768, 704x480/576, 640x480, 320x240
<i>Frame Rate</i>	Max. 30/25fps (NTSC/PAL)
<i>Streaming</i>	Triple Stream: H.264x/H.265x2, MJPEGx1
<b><u>SYSTEM</u></b>	
<i>Video Contents Analysis</i>	Tampering
<i>Motion Detection Area</i>	16 Programmable Area (Include Area 8, Exclude Area 8)

**ANNEX B**

<i>Privacy Mask Zone</i>	4 Programmable Zone
<i>Smart Codec ROI</i>	8 Regions
<i>FTP Uploading</i>	MJPEG
<i>Event Notification</i>	E-mail, FTP, Notification Server, XML Notification
<i>Login Authority</i>	Administrator, Operator, Guest
<i>Event Buffering FTP</i>	Pre: 30sec, Post: 30sec
<i>Manual Trigger</i>	4 Programmable Trigger
<i>Security</i>	Multi User Authority, IP Filtering, HTTPS, SSL
<i>Network Time Sync</i>	NTP Server, Synchronized Computer, Manual
<i>Software Reset</i>	Restart, Reset, Factory Default
<i>Hardware Factory Reset</i>	Yes
<i>Auto Recovery</i>	Backup, Restore
<i>Remote Upgrade</i>	Web Browsing (IE, Chrome, Safari, Firefox), SmartManager
<b><u>NETWORK</u></b>	
<i>Protocol</i>	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, QoS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
<i>Client Software</i>	Web, SmartManager, Client S/W, Mobile S/W
<i>Max. User Connection</i>	Live: 10 users, Playback: 3 users
<i>API Support</i>	Open API, Onvif Compliance
<i>Mobile Support</i>	Android, iOS
<b><u>EXTERNAL IN/OUT</u></b>	
<i>Ethernet</i>	RJ-45(10/100Base-T)
<b><u>ETC</u></b>	
<i>Operating Humidity</i>	95% or less (Non-Condensing)
<i>Operating Temperature</i>	-20~+50°C
<i>Power Supply</i>	PoE/12VDC
<i>Power Consumption</i>	145mA(7W)@PoE / 480mA(5.8W)@12VDC
<i>Dimension</i>	81(W)x82(H)x239(D)mm
<i>Net Weight</i>	Approx. 680g
<i>Ingress Protection</i>	IP66

3. Does the contract price in the quotation include costs for installation (labor and materials?): (Yes/No) \_\_\_\_\_

\_\_\_\_\_  
 Kindly affix your seal or signature  
 in the space provided above